


NARISHIGE

MM-94B

Motor-drive Manipulator

MM-94 for right and left-side

MM-94B is an add-on type manipulator for left-side use of MM-94, that is used with a control unit of MM-94. For the full setup with right and left-side, MM-94 and MM-94B share one control unit.



* MM-94B is left-sided model.

Control Unit



Since MM-94B does not include control unit, MM-94 is required to use MM-94B.

For left-side use without control unit, please contact us.

Specification

Accessories included		Hex Wrench
Movement range	Coarse	X22mm, Y22mm, Z22mm
Driving speed	X/Y axis	1.4mm/s (with use of high-speed button) Maximum speed 0.7mm/s (with use of speed adjusting knob) Minimum speed 0.1mm/s (with use of speed adjusting knob)
	Z axis	2.8mm/s (with use of high-speed button) Maximum speed 1.4mm/s (with use of speed adjusting knob) Minimum speed 0.2mm/s (with use of speed adjusting knob)
Working voltage		Refer to control unit of the MM-94
Power consumption		Refer to control unit of the MM-94
Dimensions/Weight	Controller	W70 × D100 × H120mm, 530g, Connecting cable (1.2m)
	Drive unit	W85 × D112 × H144mm, 591g, Connecting cable (1.2m)

Specifications are subject to change without notice.

Copyright © NARISHIGE Group. All Rights Reserved. 1999-2025